



PATIO & BLOCK PAVING SEAL

Thompson's Patio & Block Paving Seal delivers a durable, waterproof seal that enhances and protects your patio.



COMPOSITION

Thompson's Patio & Block Paving Seal is a water-based acrylic formulation.

Physical Properties		
Re-Coat Time		2Hrs
Dry Time		4Hrs
Drive over time		24Hrs
Coverage	Per L	6m ²
VOC	Low	0.3% - 7.99%
Appearance		Milky, White
Odour		Low Odour
SHEENS		Wet Look, Satin
SIZES		5L

AREAS OF APPLICATION

Granite, cast, sandstone, limestone, block paving, flagstones and matt/ unglazed tile – NOT RECOMMENDED FOR USE ON BLACK LIMESTONE

PREPARATION

Make sure block paving, jointing sand and paving slabs are dry before you start. Give the surface a decent scrub with a stiff bristle brush to remove any dust or dirt. If you have any mould or algae staining clean the surface before sealing using Thompsons Advanced Patio & Block Paving Cleaner. Make sure any cleaners are rinsed off the patio and the surface is dry before sealing.

APPLICATION

For Best results use on a dry day above 10°C. Give the tin a really good shake. Pour the tin into a roller tray and use a long pile roller to apply in long strokes. On textured surfaces, make sure any puddles are spread into dry areas. Wait 2 Hours before putting on the second coat. Really rough surfaces might need an extra coat.

COVERAGE

Approximately 6m² per litre. Coverage rates vary with the porosity and roughness of the surface. The levels quoted are based on average performance. A site Trial is recommended.

DRYING TIME

Thompsons Patio & Block Paving Seal should be Re-coated after 2 hours. Will dry be touch dry in approximately 1 hour Depending on the weather and type of surface, It can be walked over after 4 hours & can be parked on after 24 hours.

CLEANING OF TOOLS

Remove as much product as possible from application equipment prior to cleaning. Clean equipment with warm soapy water.

IMPORTANT NOTES

- Always read the instructions carefully before use
- Allow new patios to weather for at least one month before coating with Thompsons Patio & Block Paving Seal
- Apply when air or surface temperature is above 10°C
- Don't apply if it's raining or forecast to rain
- The sheen level will be dependent on the type & nature of the patio or block paving
- **The colour & appearance of the patio or block paving can change colour significantly with the application**
- **Always test on a small inconspicuous area first before coating the whole area**
- **Caution: surface may be slippery when wet**
- Avoid spillage onto surrounding vegetation and protect garden furniture

STORAGE

Store in a cool, dry, well-ventilated place away from heat and sources of ignition. Ensure container is fully re-sealed after use. To avoid the risk of spillage always store and transport in a secure and upright position. The shelf life of the product in sealed containers is 2 years.

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants

HEALTH AND SAFETY

Follow and observe all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonswaterproofing.co.uk

Web: www.thompsonswaterproofing.co.uk

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services