


Thompson's®
THE WATERPROOFING EXPERTS

EMERGENCY LEAK FIX



Thompson's Emergency Leak Fix is a clear flexible sealant for use on leaking gutters, pipes and weather damage to doors and windows. It can be applied direct to damp surfaces and over painted.

COMPOSITION

A polymer blend within a solvent mixture.

AREAS OF APPLICATION

Suitable for use on wood, plastic, glass, upvc, brick, stone, roof felt & tiles.

PREPARATION

Use a stiff bristle brush to remove any dust, dirt or algae. Give the area a light sand.

APPLICATION

Cut the nozzle at a 45 degree angle to a width matching the gap you're going to seal. Fit the cartridge into a standard sealant gun. Apply slowly and evenly at an angle to the repair, making sure it covers both sides of the repair. If you're joining gutters, apply sealant to both surfaces and press them together. Smooth down with a wetted spatula.

DRYING TIME

Curing time will vary with depth of repair. Low Temperatures and high humidity will lengthen curing times.

CLEAN UP

All equipment should be cleaner using white spirit.

IMPORTANT NOTES

Apply in accordance with the coverage guidelines otherwise product performance will be reduced

STORAGE

Store in a cool, dry, well ventilated place away from the heat and sources of ignition and direct sunlight. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost. The shelf life of product is 24 months from date of manufacture when stored in temperatures below 30°C

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use Shown on the pack. Specific health and safety data sheets Are available on request.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

Physical Properties

Physical Properties		
Coverage	Per 6mm Bead	11m
VOC	High	25-50%
Tack Free Time	15 Minutes	
Skin Time	5 Minutes	
Cure Rate	3mm per 24 hours at 23°C and 50% RH	
Application Temperature	5°C to 40°C	
Service Temperature	-40°C to +80°C	
Shore A Hardness	10	
Specific Gravity	0.95	
Tensile Strength	0.5MPa	
Elongation	400%	
Appearance	Colourless viscous liquid	
Odour	Characteristic, Organic solvents	
Viscosity	Structured	
SPECIFICATIONS		
ISO 9001		
SIZES	310ml	
COLOURS	Clear	

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonswaterproofing.co.uk

Web: www.thompsonswaterproofing.co.uk

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.