



Thompson's®

THE WATERPROOFING EXPERTS

ONE COAT CONCRETE SEAL

Thompson's One Coat Concrete Seal is a highly durable, stain resistant clear coating designed to seal, stabilise & protect concrete surfaces. It also repels water, oil, grease and fuel spills.



COMPOSITION

Solution of acrylic resins in aromatic hydrocarbon solvents. Contains no added lead.

Physical Properties		
Dry Time		1Hr
Heavy Traffic		24Hrs
Coverage	Per L	6m ²
VOC	Very High	>50%
Appearance		Colourless liquid
Odour		Solvented
SIZES		5L

AREAS OF APPLICATION

Suitable for use on Garage floors & Concrete drives or paths.

PREPARATION

Give the concrete a scrub with a stiff bristle brush, remove any dust or dirt. Open any windows or garage doors for ventilation. Use Thompson's Oil & Drive Cleaner to give the concrete a good clean before application. For existing oil or grease stains, use this neat. Make sure any cleaners are rinsed off the concrete & it's dry before applying One Coat Concrete Seal.

APPLICATION

On Cold & Damp Days, drying and re-coat times will take longer. For best results, use on a dry day above 10C. Give the tin a good shake. Pour the tin into a roller tray and use a long pile roller to apply in long smooth strokes. If you're sealing your garage floor, start from the furthest point and work towards the door. Apply an even coat, making sure that any puddles are spread into dry areas. For more porous concrete you might need to apply another coat after 4 hours.

COVERGAE

Coverage will depend on the texture & type of surface you're coating.

DRYING TIME

Thompson's One Coat Concrete Seal will be touch dry in approximately 1 hour. Light traffic is acceptable after 4 hours. Heavy traffic is acceptable after 24 hours. Dry time can vary depending on cold & damp conditions.

MAINTENANCE

Treated areas may be re-coated as required. Exterior surfaces may require re-treatment every 1-2 years depending on use.

STORAGE

Store in a cool, dry, well-ventilated place away from heat and sources of heat, sources of ignition and direct sunlight. To avoid risk of spillage, always store and transport in a secure and upright position. Keep container tightly closed. The shelf life of the product in airtight containers will be at least 3 years.

CLEANING OF TOOLS

Remove as much product as possible from application equipment before cleaning. Clean brushes, rollers and any other equipment immediately after use with a proprietary paint brush cleaner. Remove as much product as possible from equipment prior to cleaning.

IMPORTANT NOTES

- Always read the label carefully before use
- Don't apply if it's raining or forecast to rain
- Allow new concrete to cure for up to 30 days before applying
- Do not use Thompson's One Coat Concrete Seal in the home unless maximum ventilation is possible, during and after application. For further details please contact Thompson's Technical Services
- Thompson's One Coat Concrete Seal dries to a satin sheen. The level of sheen depends on the type of concrete you're coating
- The colour and appearance of your concrete can change significantly after coating. Always test an inconspicuous area prior to coating.
- Avoid spillage onto surrounding vegetation and protect garden furniture
- Avoid contact with plastic and rubber materials (Including footwear) whilst wet
- Remove any splashes whilst still wet with white spirit

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonswaterproofing.co.uk

Web: www.thompsonswaterproofing.co.uk

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depends on factors beyond our direct control. Standard codes of painting practice should be followed.

DATA SHEETS

Data sheets on other Thompson's products are available on request from our Technical Service Department.